



AEROK®

PYROK®

Material Technical Data Sheet FORMOA SURFACE ACTIVATOR Reviewed on 24 April 2003

TECHNICAL CHARACTERISTICS

Base	Solvents and special activating agents
Consistency	Liquid
Specific Gravity	0.78g/ml
Flash Point	13°C

PRODUCT

Formoa Surface Activator is at the same time: a cleaner, degreaser and primer. Formoa Surface Activator will activate non porous surfaces, such as: plastics, coatings and metals for improved adhesion of sealants based on silicone, polyurethane and MS Polymers®.

CHARACTERISTICS

- Liquid, easy application
- To be used as a cleaner / primer on non porous surfaces
- Suitable for silicone, polyurethane and MS Polymer® based sealants and adhesives

APPLICATIONS

Preparation of plastics, powdercoatings and other non porous surfaces before bonding and sealing

FORMOA®

FORBOND®

PUROK™



SHELF LIFE

6 months in unopened packaging, in a cool and dry storage place at temperatures between +5°C and +25°C.

SURFACES

Type: All non porous surfaces

We recommend preliminary compatibility tests previous to application.

APPLICATION

Method: Apply with a clean lint free cloth

Recommendation: Apply in one direction. Replace cloth regularly in order to avoid contamination of the surfaces. By doing so the surface is cleaned, degreased and activated for the application of a sealant. Leave to evaporate for 5 minutes. Apply sealant / adhesive not later than 2 hours after application.

HEALTH AND SAFETY RECOMMENDATION

Apply the usual industrial hygiene
Wear gloves and goggles

Remarks:

Formoa Surface Activator can be applied to a wide variety of non porous substrates. Due to the fact that specific substrates, such as: plastics, polycarbonates, etc, may differ from manufacturer to manufacturer we recommend preliminary compatibility tests.

AEROK[®]

PYROK[®]

FORMOA[®]

FORBOND[®]

PUROK[™]

